

Laqvin Fast Dry BB Systems

Pre-finishing systems for Burnblock impregnated wood.

Laqvin Fast Dry BB is a special system developed for coating exterior cladding which has been treated with Burnblock fire-retardant impregnation. The **Laqvin Fast Dry BB** system is designed to protect exterior cladding against outdoor conditions such as adverse weather.

Laqvin Fast Dry BB in combination with special adhesion primer **SX1420** provides very good adhesion and flexibility which results in very good protection to exterior cladding against outdoor conditions.

Laqvin Fast Dry BB EG1570-xxxx must always be used with **SX1420** and finishing instructions are to be strictly followed.

To achieve long term exterior durability, after installation of pre-finished cladding all ends, cuts and holes must be sealed with **EG1570-xxxx**, and it needs to be decorated with topcoat EG1570-XXXX.

Products:

Product Code	Name	Description
SX1420	LAQVIN TON	Primer
EG1570-XXXX	LAQVIN FAST DRY BB	Topcoat

Examples of finished system:

System	Product Code	Application Amount (g/m)	Drying	Period to redecoration
Pre-finishing	SX1420	According to Burnblock spec.	According to Burnblock spec.	Immediately after installation, not later than within 3 months or factory finish.
	EG1570-XXXX	According to Burnblock spec.	According to Burnblock spec.	
Factory finished				
Pre-finish + additional layer	EG1570-XXXX	According to Burnblock spec.	According to Burnblock spec.	Up to 5-10 years
Recoating after installation				
Recoat on site	EG1570-XXXX	+/- 100 gr/m ²	Ambient drying	Up to 5-10 years

Maintenance of finished system:

System	Product Code	Inspection	Maintenance
Pre-grey 1 layer system	SX1420-XXXX	Wear and Tear effect	No maintenance
Finished system	SX1420	Inspection every 2 years (1.1)	Maintenance every 5 years (*) (1.2)
	EG1570-XXXX		

(*)with EG1570-XXXX or a good quality water based acrylic topcoat suitable for exterior use.

1.1 Checking the entire object/project on any weathered and/or damaged areas. If necessary, clean and touch up.

1.2 Clean the surface, sand lightly in places where there is weathering. If sanding is through the entire paint system, then SX1420 is required before EG1570-XXXX; pre-treat these areas twice. Re-treat the entire object 1 time with EG1570-XXXX (*)

FYI: Fire impregnated goods may display salt extraction and wood-strip markings, this must be accepted. Pls. refer to our general terms and conditions.

Exceptions. The Company's warranty does not cover errors or defects due to: (i) normal wear and tear, (ii) lack of maintenance in accordance with the paint manufacturer's commissioning or maintenance instructions (iii) use contrary to the Company's instructions or common practice or for non-agreed purposes, (iv) errors or defects which can reasonably be attributed to underlying materials like damage due to the seepage of resin or tannin, damage due to knots or previous treatments (v) remedy or change carried out by others than the Company, or (vi) other conditions for which the Company is not responsible.

Please note that the application of the Laqvin Fast Dry BB system must be in accordance with the Burnblock specification provided. Application of excessive additional layers of topcoat can reduce the fire-retardant properties of the cladding.

Sherwin-Williams Sweden AB

2023-12-04



SHERWIN-WILLIAMS

Performance Coating Group

Jacek Królikowski

Product Manager Interior Building Products